

Problem Area Linkages






Single Purpose Model






Single Purpose Model






Multi-Purpose Model

Resource Management






Resource Management Model







early Total Delta Outflow

Historical Monthly Outflow Range

High

15,670,000 acre feet March 1983

Low

179,000 acre feet September

Average

1,197,000 acre feet



Hydrological Variability

Annual


Seasonal

Daily

Impact/Value Variability



Disposition of Sacramento and San Joaquin River Flows



% Depletion by Year Type

• Wet 24%


Above Normal 41%

Below Normal 55%


• Dry 56%

• Critical 65%






Critical Years Average Monthly Delta Outflow






Dry Years Average Monthly Delta Outflow






Wet Years Average Monthly Delta Outflow





Average Monthly 73 Year Delta Outflow





Resource Management Concept

Resource Conflicts

Increase Resistance to Impacts

Seek Multi-Objective Strategies



Water Management Concept

Reduce Conflict

Increase High Value Benefits

Shifting Diversion Patterns



Water Management Tools

- ERPP
- Storage
- Conveyance
- Levee Stability
- Water Quality
- Water Transfers
- Water Use Efficiency
- Watershed Management



Water Use Efficiency

- Provide Water to Meet Currently Unmet or **Future Needs**
- Reliability Net Improvements for Water Supply
- Can Improve Water Quality and Reduce Ecosystem Impacts



Water Transfers

 Effective Means of Moving Water Between Users on a Voluntary and Compensated Basis

Water for Environmental Purposes

 Net Improvements for Water Supply Reliability



Storage

- Low Value Water into High Value Water
- Attenuate Flood Flows
- Shift Diversions to Reduce Entrainment
- Low Impact Diversions for Increased Supplies or Greater Environmental Flows
- Improve Water Quality



Conveyance

Increase Operational Flexibility

Reduce Diversion Impacts

 Improve Water Quality in Export Regions



Ecosystem Restoration Program Plan

Rehabilitate the Ecosystem

Reduce Conflicts with Water Diversions

Reduce Conflicts with Land Use



Levee Stability

Improve Water Supply Reliability

Improve Land Use and Associated **Economic Activities**

Improved Water Quality Reliability

Improved Ecosystem Health



Watershed Management

Improved Water Quality

Increased Water Supply



The Basic Concept of Time Value is Valid

Increase Supply

Existing Supply

Reduced Supply




Example Illustrating Storage

Offstream

Conjunctive Management




Wet Years Average Wonthly Delta Outflow






Dry Years Average Monthly Delta Outflow









Assumptions for this Example


Storage does not exceed 5,000 CFS. The Diversion Rate to Offstream


downstrem plan and diversion diverted to insure ability to meet requirements. Flows below 25,000 CFS are not




















CALFED Alternatives

Each Integrates All Tools



CALFED Bay-Delta Program Service Area Drought Year Demand Management Projections - Water Use Effeciency Potential




Figure 6

^{1.} Supply and demand values are from draft Bulletin 160-98 and have been adjusted to reflect the Central Valley Watershed (North Coast Rivers are excluded).

2. Demand range includes adjustments from baseline for existing water conservation measures and reduced agricultural acreage plus potential AFRP and ERPP needs.

-Proper Balance-What is the Appropriate Role:

of Storage?

of Demand Management?



Why Develop Storage?

Storage turns low value water into high value water.

- Attenuate flood flows.
- Shift diversions to reduce entrainment.
- Low impact diversions for increased supplies or greater environmental flows.
- Improve water quality.



Why is Storage in every CALFED Alternative?

- Sometimes there is no acceptable substitute.
 - Major changes in diversion patterns to reduce entrainment are very difficult to achieve without increased local storage.
 - Storage allows for easier real-time environmental operations.
- Alternatives exist to storage in some cases, but can they carry full load?
 - Water transfers and water efficiency measures should be part of solution.
 - However, potential for these measures unclear.
 - Local impact unclear. Large-scale land retirement not an acceptable option.
- Storage provides assurances. More flexibility means less conflict
- Recommendation for including storage represents a planning umbrella, not a storage target.



Upstream Storage

Onstream storage

- Easy to fill and empty.
- Increase instream flows, dry year supplies, flood control, temperature control and hydropower.

Offstream surface storage

- More limited input/output capacity.
- Increase instream flows, dry year supplies, flood control, temperature control.
- Modify local diversion patterns to reduce entrainment.

Groundwater storage

- Similar to offstream surface storage, but....
- Lower input/output rates.
- Groundwater-surface water interactions can impact local users and reduce benefits in areas with high water tables.



Storage in Export Areas

Off-Aqueduct Surface Storage Fill during low impact periods. Use for:

- Increased exports
- Reduced entrainment
- San Joaquin Valley wetlands
- Increased San Joaquin River flows
- Improved water quality in the export areas
- Increased security against major outages in the Delta
- Export constraints limit ability to fill.
- Near-Delta storage less constrained if they have their Delta intakes.



Storage in Export Areas - cont

Groundwater storage
Like off-aqueduct surface storage, but...

- · limited canal capacity.
- limited local distribution capacity.
- · low rates of input and output of water.



Phasing/Sequencing Alternatives

It may be possible to sequence the development of storage to assure an appropriate amount.

For example:

- · Acquire easements.
- Develop storage to meet needs that cannot reasonably be met without storage.
- Set reasonable limits on the transferability of water.
- If additional water needs remain, pursue acquisition of additional storage.



- Land Retirement to Reduce Water Demand Not Not Included in Phase II Draft Alternatives
- Additional Analysis Needed to Move Forward
 - Some Stakeholders Advocate Inclusion
 - Clean Water Act 404 (b) (1) Analysis
- Significant Public Policy Issues Not Conveyed in this Technical Analysis



- Request Comments from Stakeholders ASAP
 - Technical: Are Our Numbers Right?
 - Policy: Significance of Impacts, Failure to to meet Solution Principles

We will Continue to Refine Analysis



Analysis Results:

- Retire 500,000 Acres in San Joaquin Valley
- Net Water Savings About 1.4 MAF/Yr.
- Cost About \$2.25 Billion Plus O&M
- Water Cost Range \$60 to \$300 Per Acre-foot Average \$150/af



Regional Distribution of Retired Land

Delta Mendota Service Area	170,000 acres
Westlands Area Tulare Lake Bed	120,000 acres 140,000 acres

(Acreage allocation based on drainage-impacted lands identified in "Rainbow Report")

Analysis of Impacts Used CVPM, IMPLAN Models



Cropping Reductions:

Cotton 230,000 acres
Field Crops 150,000 acres
Alfalfa Hay 100,000 acres
Vegetables 15,000 acres
Rice, Trees, Vines 5,000 acres

- Annual Loss in Personal Farm Income: \$160 million
- Annual Loss in State and Local Taxes: \$16 million
- Job Loss: 6400 (Nearly 22,000 Lost, Over 15,000 Gained)

